



CEILING FAN SUBMITTAL SHEET

Project: _____

Date: _____

Engineer: _____

Architect: _____

Submitted By: _____

CEILING FANS TO BE FURNISHED AS SPECIFIED:

- UL Listed and Approved. Holographic UL Label applied to motor housing.**
- UL Approved as Sprayproof. Documented approval by UL Laboratories Water Spray and Humidity Test.**
- One way condensation release plug installed on bottom of motor housing.**
- 3 year warranty for agricultural applications.**
- All metal construction – no plastic.
- Triple neoprene seals – neoprene deflection boot, neoprene sealed motor case, and twist lock cap on neoprene sealed downrod.
- Corrosion resistant prime and finish coats on all metal housings and blades.
- Precision balanced lightweight aluminum blades with aerodynamically curved tip.
- Totally enclosed, heavy duty motor with resistance protection.
- Permanent, sealed, high heat resistant bearings with special high temp lubricant.
- High grade silicone steel motor laminations for maximum energy efficiency.
- 9.5 mf non-polar, weatherproof, encapsulated, extra heavy-duty capacitor.
- Pre-wired with 16” cord and molded 3 prong plug with built in strain relief.
- Maximum RPM of 330.
- 43,500 CFM.
- Full 60” blade sweep.



CEILING FAN MODEL

Model Number: 190A-7 60” Northwest Agrifan

Manufacturer: Northwest Envirofan

Contact: Janet F. Dahl 800-236-7080 www.envirofan.com